



## **EMC-4 PAINT STRIPPER**

### **PRODUCT DESCRIPTION**

EMC-4 is a very powerful and very fast acting paint remover that aims to be super effective and perform better than its competition in the market. The formulation based on unique combination of solvents and special additives to perform better and strip the paint without affecting the substrate.

EMC-4 is specially formulated by keeping professionals in mind. It can be used to strip away years of old coatings and is one of the strongest paint strippers in the market. Perfect for removing numerous layers of coatings and varnish quickly and efficiently and can be cleaned up relatively easy.

EMC-4 can be used to remove layers of tough coatings from wooden surface like old furniture & from metal surfaces like cars, bikes, bus, truck, fans, etc employed in wide area of industrial applications like paint shops, workshops, garages, etc.

It offers impressive performance on two pack wood finishes, air drying, melamine, polyamides, polyurethane, polyester & powder coating.

You can also dilute EMC-4 with our NC Thinner with almost no loss in performance when apply on metals. This will save cost & labour work while improving the stripping performance.

## **APPLICATION GUIDE**

- 1. Area of Application : Metal, Wood, Plastic
- 2. Appearance : Thick Solution
- 3. Method of application : Apply by brush or spray
- 4. Stripping time : 5 mins. Depends on layers & coating type
- 5. Flammability : Yes
- 6. Packing : 500 ml, 1 Liter, 5 Liters, 20 Liters

## **DIRECTION FOR USE**

1. Lightly sand the surface with coarse emery paper for better stripping action.
2. Stir the contents of EMC-4 paint stripper nicely. Don't shake the container.
3. Apply heavy coat of EMC-4 liberally with the help of paint brush on the surface.
4. Allow the paint stripper to be on surface for 5-7 minutes for the paint of surface to be softened and blistered. The Stripping time depends on the type & layers of coating.
5. Remove the swell paint film by gently scrapping with putty knife with ease.
6. Container should be closed after every use.

## **NOTES**

1. The product doesn't affect on rubber and chromium.
2. Handle products in good ventilation.
3. Avoid inhaling the vapors as the product contains volatile organic compounds.
4. Thicker the coat of EMC-4 , Stronger will be the stripping action.

## **STORAGE & SAFETY MEASURES**

1. Store the product in ambient conditions in well ventilated location and away from source of ignition and fuel.
2. Use rubber/polyurethane gloves, safety goggles/glasses and safety masks while handling paint.
3. Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist.
4. Do not dispose in any drain or land filling.
5. Avoid eye and skin contact.
6. Product is flammable.